



## MFA – Outdoor LED Area Floodlight



### Specification:

- Input Voltage: 120~277V
- PF: ≥ 0.9
- THD: < 20%
- CCT: 4000K & 5000K
- CRI: 70+
- Dimming: 0-10V Dimmable
- L70: ≥ 50,000 hours

### Applications:

- Area Lighting
- Site Lighting
- Parking Lot Lighting

### Features:

- Durable & anti-rust coating
- Aluminum die-cast housing
- High efficiency
- Type 3 beam spread
- Operating under -20 °C ~ 50 °C ambient condition
- Multiple mounting options and 4", 5" and 6" round pole adaptor available
- Intelligent control sensor available
- UL and DLC Listed
- Five-Year Limited Warranty

### Lumen Package:

Lumens	Watts	LPW	Equivalent Watts
19,073	177	107	400 ~ 750
24,010	239	100	750 ~ 1,000

Series	Watts	CCT	Dimming	Options
MFA	180W	40K	0-10V (Blank)	OS (Control Sensor)
	240W	50K		SF (Slip Fitter)
				U (Yoke Mount)
				EA6 (6" Extruded Arm)

## Mirus Lighting, Inc.

9120 Center Ave, Rancho Cucamonga, CA 91730  
 Tel: 1-800-255-8990 E-mail: [sales@miruslighting.com](mailto:sales@miruslighting.com)

