



MFD – Outdoor LED Floodlight



Specification:

- Input Voltage: 120~277V
- PF: ≥ 0.9
- THD: < 20%
- CCT: 4000K & 5000K
- CRI: 70+
- Dimming: Non-Dimmable
- L70: ≥ 50,000 hours

Applications:

- Area Lighting
- Security Lighting
- Perimeter Lighting
- General Site Illumination
- Signage Lighting

Features:

- Durable & anti-rust coating
- Aluminum die-cast housing
- High efficiency
- Operating under -20 °C ~ 50°C ambient condition
- ½” knuckle mount (29W)
- Yoke-style mount (13W, 28W, 50W)
- UL and DLC Listed
- Five-Year Limited Warranty

Lumen Package:

| Lumens | Watts | LPW | Equivalent Watts |
|--------|-------|-----|------------------|
| 1,301 | 13.5 | 96 | 75 |
| 3,010 | 28.0 | 107 | 175 |
| 3,336 | 30.0 | 111 | 175 |
| 5,621 | 50.0 | 112 | 250 |

| Series | Watts | CCT | Dimming | Mounting Style |
|--------|-------|-----|---------|----------------|
| MFD | 13W | 40K | (Blank) | Yoke |
| | 28W | 50K | | Yoke |
| | 50W | | | Yoke |
| | 29W | | | ½” Knuckle |

Mirus Lighting, Inc.

9120 Center Ave, Rancho Cucamonga, CA 91730
 Tel: 1-800-255-8990 E-mail: sales@miruslighting.com

