



MWP – Outdoor LED Wall Pack



Features:

- Durable & anti-rust coating
- High efficiency
- Shatter resistant glass
- Operating under -20 °C ~ 50°C ambient condition
- Optional photocell, controls and visor available.
- UL and DLC Listed
- Five-Year Limited Warranty

Specification:

- Input Voltage: 120~277V
- PF: ≥ 0.9
- THD: < 20%
- CCT: 4000K & 5000K
- CRI: 70+
- Dimming: 0-10V
- L70: ≥ 50,000 hours

Applications:

- Area Lighting
- Perimeter Lighting
- Entryway Lighting
- Security Lighting

Lumen Package:

Lumens	Watts	LPW	Equivalent Watts
3,004	28.0	107	175
4,775	42.0	113	175 ~ 250
7,127	59.0	120	250 ~ 400
10,373	79.0	131	400 ~ 575

Series	Watts	CCT	Dimming	Options
MWP	28W	40K	0-10V (Blank)	CS (Cut-Off Shade)
	42W	50K		PC (120V-277V)
	59W			
	80W			

Mirus Lighting, Inc.

9120 Center Ave, Rancho Cucamonga, CA 91730
 Tel: 1-800-255-8990 E-mail: sales@miruslighting.com

