





Type:

Project:

## MINI LED L-BAR MODULE

Ra83



### Features and Benefits:

- High efficiency Class 2 LED light engine
- Slim and narrow width (~1.26 inch), optimized for luminaire design
- High color rendering and < 3 SDCM color consistency
- Modular future-proof design
- Uses the same terminal and aluminum extrusion design as standard L-Bar
- Available in SLO or HLO glare controlled lens
- Projected L90 > 36,000 h per IES TM-21
- 5 year limited warranty

### Retrofit Applications:

- Industry
- Office
- Retail

Model Number	CCT	Form Factor	Maximum Input mA	Input VDC	Output Power	LPW	Projected L70
LR024	27/30/35 /40/50	2ft	700	18	12.5W	120	>50,000 h
LR025	27/30/35 /40/50	4ft	700	36	25.0W	130	>50,000 h
LR026	27/30/35 /40/50	4ft	700	24	16.8W	130	>50,000 h

\* Min. Ambient Operating Temp: -22°F/-30°C. Max. Board Temp: 185°F/85°C.

### Mirus Lighting, Inc.

9120 Center Ave, Rancho Cucamonga, CA 91730  
 Tel: 1-800-255-8990 E-mail: [sales@miruslighting.com](mailto:sales@miruslighting.com)

