



## ORBIS – Round LED Surface Mount



Ra83

### Features:

- Quarter-turn easy installation
- Patented high efficiency visual comfort optic
- Standard 5% uplight feature
- Suitable Ta -40°C to 50°C
- Integrated sensor & daylight harvesting available
- Five-year limited warranty
- ETL Listed

### Specification:

- Diameter: 16"
- Input Voltage: 120~277V
- PF: ≥ 0.9 at full load
- THD: < 20% at full load
- CCT: 3000K, 4000K & 5000K
- Dimming: 0-10V
- Optic: Type V Distribution

### Applications:

- Parking Garage, Canopy and Low Bay

### Lumen Package:

Lm	W	LPW	L85
9,090	72.56	125	> 50,000h
7,198	57.81	124	> 50,000h
4,565	37.51	121	> 50,000h

- Projected L85 Life Hours per IES TM-21

Series	Diameter	Watt	CRI-CCT	Options
ORBIS	16	40W	*830K	S
		60W	840K	
		80W	850K	

\* Special Order CCT

## Mirus Lighting, Inc.

9120 Center Ave, Rancho Cucamonga, CA 91730  
 Tel: 1-800-255-8990 E-mail: [sales@miruslighting.com](mailto:sales@miruslighting.com)

